

## VG Exe 7J (Ex plastic cable gland 7J Exe) VG M32 EXE 19-25 CR 7J

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Polyamide cable glands, which are suitable for usage in explosion risk zones Ex e (increased safety) and Ex i (intrinsic safety).

On account of the enhanced EN60079-0:2009 testing requirements, there is now a version update of the standard (EN60079-0:2012) available.

Weidmüller offers a product family without restrictions and besides compliance with standards, the cable gland excels thanks to its increased impact resistance of 7 Joule and a possible temperature range down to -60°C without restrictions.

They have been tested to the current standard and EN 60079-0:2012 directive, and besides EAC, they are ATEX and IECEx certified.

### General ordering data

Type	VG M32 EXE 19-25 CR 7J
Order No.	<a href="#">2017300000</a>
Version	VG Exe 7J (Ex plastic cable gland 7J Exe), Cable glands, M 32, 15 mm, OD min. 19 - OD max. 25 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), Polyamide 6
GTIN (EAN)	4050118400755
Qty.	20 pc(s).

**VG Exe 7J (Ex plastic cable gland 7J Exe)  
VG M32 EXE 19-25 CR 7J**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**Dimensions and weights**

Length	40.5 mm	Length (inches)	1.594 inch
Height	40.5 mm	Height (inches)	1.594 inch
Net weight	38.52 g		

**Certificate numbers cable gland**

Identification	Ex e IIC Gb, Ex tb IIIC Db IP66/68	Certificate no. cable gland (ATEX)	IMQ 13 ATEX 010 X
Certificate no. cable gland (IECEX)	IECEX IMQ 13.0003X	Certificate no. cable gland (EAC)	RU C-TR 05.B.0840

**General information**

AF size 1	42 mm	AF size 2	42 mm
Explosion protection type	Improved safety Ex e	External thread	M 32
Impact resistance	7 joules in acc. with IEC60079-0	Installation guidelines	See assembly instructions
Length of thread	15 mm	Material	Polyamide 6
Operating temperature range, max.	70 °C	Operating temperature range, min.	-40 °C
Outer cable diameter, max.	25 mm	Outer cable diameter, min.	19 mm
Pitch of thread	1.5 mm	Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.)	Seal insert	CR
Sealing	CR	Standards	IEC 60079-0, EN 60079-0, IEC 60079-7, EN 60079-7, EN 60079-31, IEC 60079-31
Torque for cap nut, max.	10 Nm	Torque for cap nut, min.	8 Nm
Torque for connecting adapter, max.	10 Nm	Torque for connecting adapter, min.	8 Nm
Torque for lock nut, max.	10 Nm	Torque for lock nut, min.	8 Nm
UL 94 flammability rating	HB		

**Classifications**

ETIM 6.0	EC000441	eClass 6.2	27-14-91-11
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-34

**Product information**

Descriptive text ordering data Please find installation and torque specifications in the assembly instructions.

**Approvals**

Approvals	CE; EAC; ATEX; IECEX; INMETRO
ROHS	Conform

**Downloads**

Brochure/Catalogue	<a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>
Engineering Data	<a href="#">STEP</a>

**VG Exe 7J (Ex plastic cable gland 7J Exe)  
VG M32 EXE 19-25 CR 7J**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Accessories**

**Brass nuts, standard, nickel-plated**



Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

**General ordering data**

Type	Order No.	Version	GTIN (EAN)	Qty.
SKMU M32 MS	<a href="#">1737020000</a>	SKMU MS (brass locknut), Locknut, M 32, 4 mm, Brass, nickel-plated	4008190956493	100 pc(s).