

VG Exi 7J (Ex plastic cable gland 7J Exi) VG M16 EXI 6-10 CR 7J

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Polyamide cable glands, which are suitable for usage in explosion risk zones Ex e (increased safety) and Ex i (intrinsic safety).

On account of the enhanced EN60079-0:2009 testing requirements, there is now a version update of the standard (EN60079-0:2012) available.

Weidmüller offers a product family without restrictions and besides compliance with standards, the cable gland excels thanks to its increased impact resistance of 7 Joule and a possible temperature range down to -60°C without restrictions.

They have been tested to the current standard and EN 60079-0:2012 directive, and besides EAC, they are ATEX and IECEx certified.

General ordering data

Type	VG M16 EXI 6-10 CR 7J
Order No.	2017690000
Version	VG Exi 7J (Ex plastic cable gland 7J Exi), Cable glands, M 16, 10 mm, OD min. 6 - OD max. 10 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), Polyamide 6
GTIN (EAN)	4050118400793
Qty.	50 pc(s).

**VG Exi 7J (Ex plastic cable gland 7J Exi)
VG M16 EXI 6-10 CR 7J**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data
Dimensions and weights

Length	29.5 mm	Length (inches)	1.161 inch
Height	29.5 mm	Height (inches)	1.161 inch
Net weight	10.12 g		

Certificate numbers cable gland

Identification	Ex e IIC Gb, Ex tb IIIC Db IP66/68	Certificate no. cable gland (ATEX)	IMQ 13 ATEX 010 X
Certificate no. cable gland (IECEX)	IECEX IMQ 13.0003X	Certificate no. cable gland (INMETRO)	DNV 12.0051 X
Certificate no. cable gland (EAC)	RU C-TR.ГБ05.В.00840		

General information

AF size 1	22 mm	AF size 2	22 mm
Explosion protection type	Intrinsically safe Ex i	External thread	M 16
Impact resistance	7 joules in acc. with IEC60079-0	Installation guidelines	See assembly instructions
Length of thread	10 mm	Material	Polyamide 6
Operating temperature range, max.	70 °C	Operating temperature range, min.	-40 °C
Outer cable diameter, max.	10 mm	Outer cable diameter, min.	6 mm
Pitch of thread	1.5 mm	Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.)	Seal insert	CR
Sealing	CR	Standards	IEC 60079-0, EN 60079-0, IEC 60079-7, EN 60079-7, EN 60079-31, IEC 60079-31
Torque for cap nut, max.	3 Nm	Torque for cap nut, min.	2 Nm
Torque for connecting adapter, max.	3 Nm	Torque for connecting adapter, min.	2 Nm
Torque for lock nut, max.	3 Nm	Torque for lock nut, min.	2 Nm
UL 94 flammability rating	HB		

Classifications

ETIM 6.0	EC000441	eClass 6.2	27-14-91-11
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-34

Approvals

Approvals	CE; EAC; ATEX; IECEX; INMETRO
ROHS	Conform

Downloads

Brochure/Catalogue	CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP