

**VPK EX 7J (Ex blanking plug, plastic, 7J)  
VP M16 EX SI 7J**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Similar to illustration**

For sealing surplus threaded holes to maintain the IP class of protection

**General ordering data**

Type	VP M16 EX SI 7J
Order No.	<a href="#">2066720000</a>
Version	VPK EX 7J (Ex blanking plug, plastic, 7J), Blanking plug, M 16, 12 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), Polyamide 6
GTIN (EAN)	4050118415438
Qty.	100 pc(s).

## Data sheet

### VPK EX 7J (Ex blanking plug, plastic, 7J) VP M16 EX SI 7J

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Length	16.3 mm	Length (inches)	0.642 inch
Height	16.3 mm	Height (inches)	0.642 inch
Net weight	2.3 g		

### Temperatures

Operating temperature range, max.	70 °C	Operating temperature range, min.	-60 °C
Operating temperature, max.	70 °C	Operating temperature, min.	-60 °C

### Classifications

ETIM 6.0	EC000451	eClass 6.2	27-14-91-11
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-35

### Approvals

ROHS	Conform
------	---------

### Downloads

Brochure/Catalogue	<a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN</a>
Engineering Data	<a href="#">STEP</a>