

**FAD**  
**FAD S5115 SL24 M****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

The front adapters for migration are connected to the old PLC and, by means of a new pre-assembled cable, to the new one. Some adapters have 2 connectors for redundancy.

**General ordering data**

Type	FAD S5115 SL24 M
Order No.	<a href="#">1985980000</a>
GTIN (EAN)	4050118371109
Qty.	1 pc(s).

**FAD  
FAD S5115 SL24 M**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	280.45 mm	Length (inches)	11.041 inch
Width	46 mm	Width (inches)	1.811 inch
Height	24.7 mm	Height (inches)	0.972 inch
Net weight	203 g		

**Temperatures**

Operating temperature, max.	50 °C	Operating temperature, min.	-25 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-40 °C
Operating temperature	-25...50 °C	Storage temperature	-40...60 °C

**Connection data**

Connection (field side)	SL 5.08 mm
-------------------------	------------

**Ratings data**

Operating voltage	250 V AC	Max. current per channel	6 A
Total operating current	32 A		

**Insulation coordination (EN50178)**

According to	DIN EN 50178	Rated insulation voltage	< 250 V AC
Surge voltage category	II	Pollution severity level	2
Insulation test voltage	1.2 kVAC		

**Classifications**

ETIM 5.0	EC002780	ETIM 6.0	EC002584
eClass 6.2	27-14-11-52	eClass 7.1	27-14-11-52
eClass 8.1	27-14-11-52	eClass 9.0	27-33-02-92
eClass 9.1	27-24-22-92		

**Approvals**

Approvals



ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">EPLAN</a>
------------------	-----------------------

**Data sheet**

**FAD**  
**FAD S5115 SL24 M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

